



SANO UK Powered Stairclimbers Ltd.

Bristol Court, Betts Avenue Martlesham Heath Ipswich, Suffolk / IP5 3RY, England

Tel.: +44 1473 / 333 889 Fax: +44 1473 / 333 742 info@sano-uk.com www.sano-uk.com

SANO Transportgeraete GmbH

Gewerbezeile 15 4040 Lichtenberg / Linz, Austria

Tel.: +43 7239 / 510 10 Fax: +43 7239 / 510 10-14

office@sano.at

f ⊚ **□** in





Strong for heavy loads



ALL ADVANTAGES AT A GLANCE

- > intuitive user panel
- > compact, light, for heavy loads
- > new powerful lithium battery with state-of-charge indicator. **Autonomy** up to **500/700 steps** up and down*
- > extremely lightweight lithium battery only 1,6 kg
- > for loads up to 360 kg*
- > up/down button for left- and right-handers
- > 2 drive modes (single/continuous step)
- > rugged frame with SANO patented aluminum profiles
- > step light for poor light conditions
- > innovative, integrated step-edge braking system
- > automatic shut-off system
- > friction clutch and electronic overload protection
- > for all types of stairs, even on spiral staircases and narrow landings
- > puncture-proof tyres

NEO LIFTKAR® HD UNI

Whether moving electrical enclosures, drinks dispensers, gaming machines, large boilers, solar heating vessels, heavy rolls of lino-leum or stacks of crates, the **NEO LiftKar HD UNI** has been specially designed to transport tall and heavy loads over every kind of stairs.

| MODEL | 220 | 330 | 360 |
|--|------------------|-----------------|-----------------|
| 2 climbing speeds | 10-15 steps/min. | 6-10 steps/min. | 6-10 steps/min. |
| autonomy (max.) steps up and down** | 700 steps | 500 steps | 500 steps |
| load capacity | 220 kg | 330 kg | 360 kg |
| max. step height | 210 mm | 210 mm | 210 mm |
| weight of base unit without battery | 35,5 kg | 35,5 kg | 35,5 kg |
| dimensions (height / width/depth) | 1615/560/485mm | 1615/560/485mm | 1615/560/485mm |



^{**}sum up/down



扁 new step light



new lithium battery





